



## Technical data **MobiMASTER ICU 402**

|                                 |  |
|---------------------------------|--|
| <b>Operating voltage</b>        | 12 VDC or 24 VDC (9 - 32 VDC)  |
| <b>Power consumption</b>        | 40 mA (standby 30 mA)  |
| <b>Operating temperature</b>    | - 20 °C to + 70 °C   |
| <b>Display</b>                  | LCD graphic display  |
| <b>Dimensions</b>               | 131 x 67 x 35 (W x H x D)  |
| <b>Weight</b>                   | 140 g  |
| <b>Interfaces</b>               | <b>standard:</b> RS485, USB<br><b>optional:</b> IBIS Slave, RS232, second RS485 Interface, digital I/O |
| <b>Editing software</b>         | MIE (MobilInfoEdit)  |
| <b>Data update</b>              | via USB flash memory   |
| <b>Memory capacity</b>          | 2 MB Flashprom   |
| <b>Standards and directives</b> | VDV 300 (IBIS)   |

### **EMC**

#### **Directive 2006/28/EC**

Type approval number  
e5\*72/245\*2006/28\*0246\*01

### **Flammability**

Directive 95/28/EC  
Regulation ECE-R118

**Modern and compact design.**

**Lightweight.**

**Logical, intuitive user navigation.**

**Easy data transfer via USB port.**

**Flexible and simple installation.**

**Optional: adapter for mounting into a standard radio slot (ISO 7736).**