



Technical data **MobiMASTER ICU 602**

Operating voltage	24 VDC (9 - 36 VDC)
Power consumption	max. 0.2 A at 24 VDC
Operating temperature	- 25 °C to + 70 °C
Display	LCD graphic display, 64 x 256 pixels
Dimensions	178 x 50 x 115 (L x H x D, installation dimensions in mm without front panel)
Weight	620 g
Interfaces	standard: RS485, digital I/O, RS232, USB optional: IBIS Slave, IBIS Master, GPS, Ethernet, Audio
Editing software	MIE (MobilInfoEdit)
Data update	manually via USB flash memory automatically via IP/Ethernet Interface (wireless and FTP service optionally available)
Memory capacity	256 MB
Standards and directives	EMC ECE-R10, Rev. 04 (EMC-Bus) Type approval number: (E5) 10R-04178 Flammability Directive 95/28/EC Regulation ECE-R118

Modern design.

Alphanumeric keyboard with highly user-friendly buttons and backlight.

IP classified front (dust and water protected), optionally also IP classified from the back.

Advanced version includes:

- Next stop information
- Voice announcement function for announcements inside and outside the vehicle
- GPS receiver
- Ethernet Interface
- Automatic triggering via GPS or odometer

Fits into a standard radio slot (ISO 7736).